



SAFETY DATA SHEET

according to regulation (EC) No. 1907/2006 (REACH), Appendix II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture Plastic Primer Spray
Registration number -
Synonyms None.
SDS number 7779
Product code Ford Internal Ref.: 185162
Issue date 26-September-2014
Version number 3.0
Revision date 15-January-2015
Supersedes date 16-October-2014
Product use Public use

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Coating.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name Ford Motor Company Ltd.
Address Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
Telephone number +44 1327 305 198
Address Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Köln
Germany
Telephone number +49 221 90-33333
E-mail HSE@rle.de
1.4 Emergency telephone number +49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F+;R12, R18, Xn;R20/21, Xi;R38

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	-------------------------------------------------------------------------------------------

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: n-butyl acetate

Hazard pictograms**Signal word**

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements**Prevention**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P261 Avoid breathing mist/vapours/spray.
 P251 Do not pierce or burn, even after use.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves.

Response

P101 If medical advice is needed, have product container or label at hand.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container to an approved waste disposal plant

Supplemental label information EUH018 - In use, may form flammable/explosive vapour-air mixture.

2.3. Other hazards The mixture contains no substance that fulfils the criteria of a PBT- or vPvB substance.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Xylene	25 - 40	1330-20-7 215-535-7	01-2119488216-32-XXXX	601-022-00-9	#, Note C, Xn; R20/21 ; C ≥ 12,5 %, Seveso 6
Classification:		DSD: R10, Xn;R20/21, Xi;R38			
		CLP: Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332			
n-butyl acetate	20 - < 30	123-86-4 204-658-1	01-2119485493-29-XXXX	607-025-00-1	Seveso 6
Classification:		DSD: R10, R66-67			
		CLP: Flam. Liq. 3;H226, STOT SE 3;H336			
Butane	10 - < 20	106-97-8 203-448-7	-	601-004-00-0	Note U, Note C, Seveso 8
Classification:		DSD: F+;R12, R18			
		CLP: Flam. Gas 1;H220, Press. Gas;H280			

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propane	10 - < 20	74-98-6 200-827-9	-	601-003-00-5	Seveso 8, Note U
Classification:	DSD: F+;R12, R18				
	CLP: Flam. Gas 1;H220, Press. Gas;H280				
Ethylbenzene	5 - < 10	100-41-4 202-849-4	02-2119752523-40-XXXX	601-023-00-4	#, Seveso 7b
Classification:	DSD: F;R11, Xn;R20				
	CLP: Flam. Liq. 2;H225, Acute Tox. 4;H332				
Chlorobenzene	0,1 - < 1	108-90-7 203-628-5	-	602-033-00-1	#, Xn; R20: C ≥ 5 %
Classification:	DSD: R10, Xn;R20, N;R51/53				
	CLP: Flam. Liq. 3;H226, Acute Tox. 4;H332, Aquatic Chronic 2;H411				

List of abbreviations and symbols that may be used above:

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

#: This substance has been assigned Community workplace exposure limit(s).

Note: Regulation No. 1272/2008 - Annex VI

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep victim warm. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed May cause drowsiness and dizziness. Headache. Nausea, vomiting. Upper respiratory tract irritation. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. Flammable or explosive mixtures with air maybe formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

6.4. Reference to other sections For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1810 mg/m3 750 ppm
	TWA	1450 mg/m3 600 ppm
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m3 125 ppm
	TWA	441 mg/m3 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	966 mg/m3 200 ppm
	TWA	724 mg/m3 150 ppm
Xylene (CAS 1330-20-7)	STEL	441 mg/m3 100 ppm
	TWA	220 mg/m3 50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Xylene (CAS 1330-20-7)	TWA	200 ppm
		442 mg/m3
	STEL	100 ppm
		442 mg/m3
	TWA	100 ppm
		221 mg/m3
		50 ppm

Biological limit values

UK. EH40 Biological Monitoring Guidance Values (BMGVs)

Components	Value	Determinant	Specimen
Xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no-effect level (DNEL)

Components	Type	Route	Value	Form	
n-butyl acetate (CAS 123-86-4)	Consumer	Inhalation	859.7 mg/m3	Short term exposure - local effects	
		Inhalation	859.7 mg/m3	Short term exposure - systemic effects	
		Inhalation	102.34 mg/m3	Long term exposure systemic effects	
		Inhalation	102.34 mg/m3	Long term Local effects	
	Professional	Inhalation	960 mg/m3	Short term exposure - local effects	
		Inhalation	960 mg/m3	Short term exposure - systemic effects	
		Inhalation	480 mg/m3	Long term exposure systemic effects	
		Inhalation	480 mg/m3	Long term Local effects	
		Consumer	Dermal	108 mg/kg/BW/day	Long term exposure systemic effects
			Inhalation	174 mg/m3	Short term exposure - local effects
			Inhalation	174 mg/m3	Short term exposure - systemic effects
			Inhalation	14.8 mg/m3	Long term exposure systemic effects
Professional	Oral		1.6 mg/kg/BW/day	Long term exposure systemic effects	
	Dermal		180 mg/kg/BW/day	Long term exposure systemic effects	
	Inhalation		77 mg/m3	Long term exposure systemic effects	
	Inhalation		289 mg/m3	Short term exposure - local effects	
		Inhalation	289 mg/m3	Short term exposure - systemic effects	

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
n-butyl acetate (CAS 123-86-4)	Not applicable	Freshwater	0.18 mg/l	Fresh water
		Seawater	0.018 mg/l	
		Sediment	0.981 mg/kg	Fresh water
		Sediment	0.0981 mg/kg	Sea water
		Soil	0.0903 mg/kg	
		STP	35.6 mg/l	
		Water	0.36 mg/l	intermittent release
Xylene (CAS 1330-20-7)	Not applicable	Sediment	12.46 mg/kg	Fresh water
		Sediment	12.46 mg/kg	Seawater
		Soil	2.31 mg/kg	

Components	Type	Route	Value	Form
		STP	6.58 mg/l	
		Water	0.327 mg/l	Fresh water
		Water	0.327 mg/l	intermittent release
		Water	0.327 mg/l	Seawater

Exposure guidelines

UK EH40 WEL: Skin designation

Ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Xylene (CAS 1330-20-7)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. Avoid inhalation of vapours or mists.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection

Wear appropriate chemical resistant gloves.

Nitrile rubber

Glove thickness 0,4 mm.

Break through time 30 - 59 min..

Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Hand protection in case of splash contact:

Nitrile rubber

Glove thickness 0,4 mm.

Break through time 30 - 59 min.

Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

The protective gloves to be used must comply with the specification of EU directive 89/686/EC and the resultant standard EN374. The above given information is based on laboratory test in line with EN374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit. Use an extra-fine particle filter of type P2.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Aerosol.

Form

Aerosol

Colour

Various.

Odour

Characteristic

Odour threshold	Not determined
pH	Not determined
Ignition temperature	365 °C (689 °F)
Melting point/freezing point	Not determined
Initial boiling point and boiling range	Not applicable, since aerosol
Flash point	< 0 °C (< 32.0 °F) without propellant
Evaporation rate	Not applicable
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1.1
Explosive limit – upper (%)	10.9
Vapour pressure	3600 hPa @ 20 °C
Vapour density	Not determined
Relative density	Not determined
Solubility(ies)	
Solubility (water)	Insoluble
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not flammable
Decomposition temperature	Not determined
Viscosity	Not available.
Explosive properties	In use, may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not available.
9.2. Other information	
Density	Not determined
VOC (EU)	749 g/l
VOC (CH)	95.95 %

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	Strong acids, alkalies and oxidizing agents.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Not available.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Not available.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Upper respiratory tract irritation. Skin irritation. May cause redness and pain.
11.1. Information on toxicological effects	
Acute toxicity	Based on available data, the classification criteria are not met.

Product	Species	Test results
Plastic Primer Spray		
Acute		
<i>Dermal</i>		> 2000 mg/kg (calcd. ATE)
<i>Inhalation</i>		> 20 mg/l, 4 hours (calcd. ATE)

Components	Species	Test results
Ethylbenzene (CAS 100-41-4)		
Acute		
<i>Inhalation</i>		11 mg/l, 4 Hours (acc. CLP 3.1.2)
Xylene (CAS 1330-20-7)		
Acute		
<i>Dermal</i>		1100 mg/kg (acc. CLP 3.1.2)
<i>Inhalation</i>		11 mg/l, 4 Hours (acc. CLP 3.1.2)

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory sensitisation	Based on available data, the classification criteria are not met.
Skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
Mixture versus substance information	No information available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
12.2. Persistence and degradability	No data is available on the degradability of this product.
12.3. Bioaccumulative potential	No data available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	The mixture contains no substance that fulfils the criteria of a PBT- or vPvB substance.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. 08 01 11 15 01 10
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not available.
Tunnel restriction code	D
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	190, 327, 344, 625
Classification code	5F

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not applicable.
Packaging instructions	203
Packaging instructions cargo only	203
14.5. Environmental hazards	No.
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Maximum net quantity packaging - Passenger and cargo aircraft	75 kg
Maximum net quantity packaging cargo only	150 kg
Maximum net quantity packaging - Limited quantity	30.00 kg
Special provisions	A145,A167,A802

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not applicable.
14.5. Environmental hazards	
Marine pollutant	No.

EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	63,190,277,327,344,959
14.8. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Not applicable.

Restrictions on use

Not applicable.

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

Other EU regulations

Category: 8

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

VOC (EU):

749 g/l

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

AC: Article category.
acc., acc.to: according, according to.
ACGIH: American Conference of Governmental Industrial Hygienists.
AFNOR: French Institute for Standards (Association Française de Normalisation).
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures).
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route).
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
AICS: Australian Inventory of Chemical Substances.
ANSI: American National Standards Institute.
AOEL: Acceptable Operator Exposure Level.
AOX: adsorbable organic halogen compounds.
approx.: approximately.
ASTM: ASTM International.
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
BAM: Federal Institute for Materials Research and Testing, Germany (Bundesanstalt für Materialforschung und -prüfung).
Maximum permissible concentration of biological working substances (BAT: Biologische Arbeitsstofftoleranzwerte).
BAuA: Federal Institute for Occupational Health and Safety, Germany (Bundesanstalt für Arbeitsschutz und Arbeitsmedizin).
BCF: Bio-concentration factor.
BET: Brunauer-Emmett-Teller.
BLV: Biological Limit Value.
BLV: Biological Limit Value (BGW: Biologischer Grenzwert, Austria).
BMGV: Biological Monitoring Guidance Value (EH40,UK).
BSI: British Standards Institution.
BS: British Standard.
BOD5: Biochemical oxygen demand within 5 days.
BOD: Biochemical oxygen demand.
bw: Body weight.
calcd.: calculated.

CAS: Chemical Abstract Service.
CEN: European Committee for Standardization (Comité Européen de Normalisation).
CESIO: European Committee on Organic Surfactants and their Intermediates (Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques).
ChemRRV: Ordinance on the risk reduction related to chemical products (ChemRRV: Chemikalien-Risikoreduktions-verordnung, Switzerland).
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction.
CNS: Central Nervous System.
CNT: Carbon nanotubes.
COD: Chemical Oxygen Demand.
CSA: Chemical Safety Assessment.
CSR: Chemical Safety Report.
DETEC: Swiss Federal Department of the Environment, Transport, Energy and Communications.
DIN: German Standards Institute / German industrial norm (Deutsches Institut für Normung / Deutsche Industrienorm).
DMEL: Derived Minimum Effect Level.
DNEL: Derived No Effect Level.
DOC: Dissolved organic carbon.
DPD: Directive 1999-45-EC / Dangerous Preparations Directive.
DSD: Directive 67/548-EC / Dangerous Substances Directive.
DSL: Canada, Domestic Substances List.
DU: Downstream User.
dw: dry weight.
e.g.: For example, for instance.
EBW: Exposure Based Waiving.
EC: European Community.
EC50: Effective Concentration 50%.
ECHA: European Chemical Agency.
EINECS: European Inventory of Existing Commercial Chemical Substances.
ELINCS: European List of Notified Chemical Substances.
EN: European norm.
ENCS: Japan, Inventory of Existing and New Chemical Substances.
EPA: United States Environmental Protection Agency.
ERC: Environmental release category.
ES: Exposure scenario.
EUSES: European Union System for the Evaluation of Substances.
EWC/EWL: European Waste Catalogue.
GCL: General concentration limit.
gen.: general.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
GLP: Good Laboratory Practice.
GW/VL: Occupational exposure limit value.
GW-kw: Occupational exposure limit value - short term.
GW-M/VL-M: Occupational exposure limit value – "Ceiling".
GWP: Global Warming Potential.
HPV: High Production Volume Chemicals.
HEPA: High Efficiency Particulate Air.
IARC: International Agency for Research on Cancer.
IATA: International Air Transport Association.
IBC: Intermediate Bulk Container.
IBC Code: International Bulk Chemical (Code) (International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk).
ICAO: International Civil Aviation Organization.
IC50: Inhibition Concentration 50%.
IECSC: Inventory of Existing Chemical Substances in China.
IMDG Code: International Maritime Dangerous Goods Code.
IMO: International Maritime Organization.
incl.: including, inclusive.
ISO: International Standards Organization.
IUCLID: International Uniform Chemical Information Database.
IUPAC: International Union for Pure Applied Chemistry.
KECI: Korea Existing Chemicals Inventory.
LCA: Life Cycle Assessment.
LC: Lethal Concentration.
LC50: Lethal Concentration 50%.
LCLo: Lowest published lethal concentration.

LD50: Lethal Dose 50%.
LEV: Local exhaust ventilation.
LOAEL: Lowest observed adverse effect level.
LOEC: Lowest observable effect concentration.
LOEL: Lowest observable effect level.
LPV: Low Production Volume Chemicals.
LQ: Limited Quantities.
Air Quality Control Regulation (LRV: Luftreinhalteverordnung, Switzerland).
TLV-STEL: Threshold limit value - Short-term exposure limit / Technical reference concentration - short-time value (TRK-Kzw = Technische Richtkonzentration - Kurzzeitwert).
Maximum allowable workplace concentration – instantaneous value (MAK-Mow: Maximale Arbeitsplatzkonzentration – Momentanwert, Austria)
Maximum allowable workplace concentration – daily mean value / Technical standard concentration – daily mean value (MAK-Tmw, TRK-Tmw : Maximale Arbeitsplatzkonzentration - Tagesmittelwert / TRK-Tmw = Technische Richtkonzentration – Tagesmittelwert, Austria).
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
MARPOL: International Convention for the Prevention of Pollution From Ships.
MTD: Maximum tolerated dose.
MWCNT: Multi-walled carbon nanotubes.
n.a.: not applicable.
N/A: Not available.
n.d.: not determined.
NLP: No Longer Polymers.
NDSL: Canada, Non-Domestic Substances List.
NF: French Norm (See AFNOR).
NFPA: National Fire Protection Association.
NIOSH: National Institute for Occupational Safety & Health.
NOAEC: No Observed Adverse Effect Concentration.
NOAEL: No observed adverse effect level.
NOEC: No observed effect concentration.
NOEL: No observed effect level.
NTP: National Toxicology Program.
NZIoC: New Zealand Inventory of Chemicals.
ODP: Ozone Depletion Potential.
OECD: Organization for Economic Cooperation and Development.
OEL: Occupational Exposure Limit.
org.: organic.
OSHA: Occupational Safety & Health Administration.
PAH: Polycyclic Aromatic Hydrocarbons.
PBT: Persistent, bioaccumulative, toxic.
PC: Product category.
PE: Polyethylene.
PEC: Predicted Environmental Concentration.
PEL: Permissible Exposure Limit.
PIC: Prior Informed Consent.
PICCS: Philippines Inventory of Commercial Chemical Substances.
PNEC: Predicted No Effect Concentration.
POCP: Photochemical ozone creation potential (Photochemisches Ozonbildungspotenzial).
POP: Persistent Organic Pollutant.
PPORD: Product and Process Oriented Research and Development.
PPE: Personal Protective Equipment.
PROC: Process category.
RA: Risk Assessment.
RAR: Risk Assessment Report.
RCRA: Resource Conservation Recovery Act.
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).
RMM: Risk Management Measure.
RTECS: Registry of Toxic Effects of Chemical Substances.
QSAR: Quantitative Structure Activity Relation.
SARA: Superfund Amendments and Reauthorization Act.
SADT: Self-Accelerating Decomposition Temperature.
SCL: Specific concentration limit.
SEA: socio economic analysis.
STEL: Short-term Exposure Limit.
STP: Sewage treatment plant.

SU: Sector of use.
SVHC: Substance of Very High Concern.
SWCNT: single-walled carbon nanotubes.
ThOD: Theoretical oxygen demand.
TOC: Total Organic Carbon.
TLV: Threshold Limit Value.
TRA: Targeted Risk Assessment.
TSCA: Toxic Substance Control Act.
TWA: Time Weighted Average.
UC: Use category.
UDS: Use descriptor system.
UEC: Use and exposure categories.
UN: United Nations.
UN RTDG: United Nations Recommendations on the Transport of Dangerous Goods.
UVCB: Unknown or Variable Composition, Complex Reaction Products, and Biological Materials.
Regulation on combustible liquids (VbF: Verordnung über brennbare Flüssigkeiten, Austria).
Regulation of the Austria Minister for Labor and Social Affairs regarding health surveillance at the workplace (VGÜ = Verordnung des Bundesministers für Arbeit und Soziales über die Gesundheitsüberwachung am Arbeitsplatz).
VOC: Volatile organic compounds.
vPvB: very Persistent, very Bioaccumulative.
WEL-TWA: Workplace Exposure Limit-Long term exposure limit (8-hour TWA(=time weighted average)reference period).
WEL-STEL: Workplace Exposure Limit-Short term exposure limit (15-minute reference period).
WoE: Weight of evidence.
WHMIS: Workplace Hazardous Materials Information System.
WHO: World Health Organization.
wwt: wet weight.
Not available.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.
R11 Highly flammable.
R12 Extremely flammable.
R18 In use, may form flammable/explosive vapour-air mixture.
R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R38 Irritating to skin.
R45 May cause cancer.
R46 May cause heritable genetic damage.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

Training information

Follow training instructions when handling this material.

Disclaimer

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Product Name: Plastic Primer Spray
Ford Int. Ref. No.: 185162

Page: 1/1
Print Date: 15.01.2015

Involved Products:

	Finiscode	Part number	Container Size:
1.	1 695 782	80SX 19L531 ME	150 ml
2.	1 771 553	80SX 19L531 MF	150 ml