



Castrol Magnatec Professional E 5W-20

Instant protection from the moment you turn the key

Description

Castrol Magnatec Professional's intelligent molecules protect from the moment you turn the key. They cling to the engine like a magnet providing an extra layer of protection, dramatically reducing* engine wear.

Castrol Magnatec Professional's unique formulation delivers protection you can see, hear and feel. With micro filtration technology and signature green colour it's engineered for today's modern engines.

Castrol Magnatec Professional. Instant protection from the moment you turn the key.

** As tested in the industry Sequence IVA wear test.*

Application

Castrol Magnatec Professional E 5W-20 is tailor made with Ford for use in their latest fuel efficient petrol engines that require a 5W-20 lubricant that meets Ford WSS-M2C948-B specification.

Advantages

Castrol Magnatec Professional's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down.
- Cling to your engine forming an extra layer that protects from the moment you turn the key.
- Bond to metal surfaces to make engine parts more resistant to wear.
- Provide continuous protection for all driving conditions, styles and temperatures.

Castrol Magnatec Professional E 5W-20 delivers superior performance under extreme cold start up conditions compared to thicker grades.

Typical Characteristics

Name	Method	Units	Castrol Magnatec Professional E 5W-20
Density @ 15C, Relative	ASTM D1298	g/ml	0.847
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.2
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	3450
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	44
Viscosity Index	ASTM D2270	None	166
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

SAE 5W-20. Meets Ford WSS-M2C948-B

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Magnatec Professional E 5W-20

04 Jan 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za